

MAG6275 Network Video Outdoor LED Screen Terminal



Description

Network Video Outdoor LED Screen Terminal adopts professional audio and video processing chip and embedded Linux operating system, stable and reliable. Using 32*64 LED dot matrix screen, it can display real-time working status and release information. The built-in high-definition camera can realize call alarm in emergency situations, and has AI alarm trigger function, which can recognize the emergency behavior of the crowd and automatically alarm. The machine can output remote audio data stream to audio signals, with intelligent host control; has a built-in MP3 player, and a SD card slot used to expand the SD card, and can be separated from the host for independent timing points; with 1 auxiliary audio output interface for connecting other amplifiers to expand the power.

Features

- Built-in 2x15W@4Ω digital amplifier
- Built-in 5W/8Ω monitor speaker and array microphone
- Support H264 encode and decode format
- Support SIP protocol for video intercom and remote paging
- Built-in echo cancellation and feedback suppression
- Built-in 2 million infrared camera, can working at night
- With AI alarm function, can automatic identify the emergency and trigger the alarm signal
- Power supply: AC220V/50Hz

Specification

Items		Specifications
Network Play	Output Sensitivity	300mV±50mV
	Frequency Response	50Hz-15kHz
	Noise	≤3mV
	SNR	≥70 dB
Maximum Output Power of Amplifier	Independent channel mode (2 channels)	10W/4Ω
Maximum Harmonic Distortion of Amplifier		≤1%
Built-in Speaker		3W/8Ω
MIC IN	Input Sensitivity	5-15mV
	Frequency Response	300Hz-3.2kHz
	Distortion	≤1%
	Noise	≤5mV
	SNR (30KHz low pass)	≥65dB
Power Supply		AC220V/50Hz
Overcurrent, Overheating, Overvoltage and Undervoltage Protection		Satisfied
Package Dimensions (L×W×H mm)		555×351×159
Machine Dimensions (L×W×H mm)		375×291×134
Gross Weight		6.5kg
Net Weight		5.5kg