

# MAG6588 Intelligent Network Paging Station



## *Features*

- 1,000 zones which can be activated
- 7-inch true color LCD display
- 1 aux input, 1 aux output and 1 headphone
- Support TCP/IP
- Users can view zone information.
- Log management and screen calibration
- The backlight on time can be adjusted to save energy.
- Shared WAN/LAN network

## *Description*

MAG6588 is intelligent network paging station allow up to 1,000 zones which can be activated by simply one button. It can realize zone based calling and group based calling. Supports TCP/IP and is compatible to shared WAN/LAN network. The system can provide 1 AUX input, 1 AUX output and 1 headphone monitoring interface to realize local extension. It provides log management and screen calibration functions. Users can view zone information. It can realize zone based calling and group based calling.

## *Specification*

<b>Rated Output Voltage</b>	1.0±0.2V
<b>MIC input sensitivity (1V output)</b>	50±10mV
<b>MIC distortion (1Kz/1V)</b>	MIC: ≤0.2%
<b>Effective frequency of MIC gain limit (±3dB)</b>	40-20000Hz
<b>MIC Signal to Noise Ratio (30K lowpass)</b>	>75dB
<b>AUX input sensitivity (1V output)</b>	300±50mV
<b>AUX distortion (1Kz/1V)</b>	AUX≤0.1%
<b>AUX Signal to Noise Ratio (30K lowpass)</b>	≥80dB
<b>Effective frequency of AUX gain limit (±3dB)</b>	20-20000Hz
<b>Effective frequency of monitoring (talkback voice) gain limit</b>	40-13000 Hz
<b>Working voltage</b>	AC180-240V
<b>Standby power consumption</b>	14.5W
<b>Package dimensions (mm)</b>	(L×W×H) 415×285×160
<b>Net Weight</b>	2kg