

DSP162HD 25W-50W High Fidelity Horn Speaker



Features

- Outputs: 25W/70V & 50W/100V
- Waterproof, IPX6
- Suitable for outdoor use
- Built-in 100v/70v transformer
- Max SPL: 121±2dB
- Wide Freq.Resp.: 250Hz-15kHz
- High sensitivity: 104±2dB
- Equipped with brackets for installation

Description

The DSP162HD is a high fidelity wall mounted speaker built-in 70v/100v transformer. The 70v/100v transformer technique reduces line losses on longer distance and allows easy parallel connection of multiple horn loudspeakers. IPX 6 waterproof level suitable for outdoor use; two-way speaker, clear sound, high sensitivity; Waterproof, made from high quality alloy-aluminum surface net

Streamline design, beautiful and durable with ABS which does not rust and it's durable;

Streamline appearance, beautiful design, advanced engineering

It is ideal choice for industrial and commercial applications in the outdoor area of train station, shopping mall, parking area and factory where background music and paging is needed.

Specification:

Model	DSP162HD
Power	25W/50W
Input Voltage	70V/100V
Sensitivity(1M,1W)	104±2dB
Max SPL(1M)	121±2dB
Freq. Resp	250Hz-15kHz
Dimension(L×W×H)	500×406×500mm
Weight	4.5kg