

WJ-32 Military Acoustic Hailing System Host



Features

- 4.3" touch screen for friendly control
- 3 modes optional music, speech and hailing
- 1 EMC Mic, 1 Driver's Mic, 1 Sub-driver's Mic, 1 Wireless Mic
- 3 audio inputs of RCA jack
- Built-in USB/Bluetooth/FM for audio source
- Built-in 1G memory, support 32G USB
- Support voice recording function
- Built-in 1 siren signal and 1 hailing signal
- 1 GSM cellphone voice input, support auto answering
- Support message TTS audio play, text to speech

Specification

Item	WJ-32
Storage Capacity	Built-in 1G, support 32G USB
Material of panel	Aluminum
AUX input sensitivity of rear panel	1Vrms
Audio balanced output of rear panel	Range: 2Vrms
	Distortion: $\leq 0.5\%$
	Noise: $\geq 90\text{dB}$
	Frequency response: 100Hz --18KHz ($\pm 3\text{dB}$)
FM frequency band range	87.0~108.0 MHz
Sensitivity of FM tuner	30dB μv
Phantom power	48V DC output
Cellphone	Only support 2G mobile web
Wireless Mic	Limited distance over 80m
Mic input sensitivity	40mVrms
Mic input frequency response	200--15K ($\pm 3\text{dB}$) Hz
Mic input mode	Support dynamic and condenser Mic (48Vphantom power)
Effective frequency range	500Hz – 10kHz (0dB)
Host rated power	< 100W
XLR balanced output voltage	1Vrms
AUX unbalanced output voltage	1Vrms
Effective frequency range limited by Mic gain	200---15K ($\pm 3\text{dB}$) Hz

Effective frequency range limited by line gain	100---18K (± 3 dB) Hz
Output voltage of built-in siren	1Vrms
Output voltage of built-in hailing	1Vrms
Size	483×370×176mm